

## Technical Data Sheet

[www.soletex.com](http://www.soletex.com)

<b>Article- No</b>	KS 053 - BERLIN (Walltex)
<b>Application</b>	Wall Covering /Interior Decoration
<b>Printable Ink</b>	Treatment applied for Latex, Uv-Curable, Solvent, Eco Solvent
<b>Material</b>	100 % Polyester
<b>Standart Sizes</b>	250 cm , 320 cm ( 98", 126" ) * 50 mt (54 yrd.)
<b>Weight</b>	220 gr ( g/m2 )+- 5(gr) (7.7 oz)
<b>Finishing</b>	Digital Coating
<b>Packaging</b>	3" paper core, wrapped with stretch film + put in a cardboard box or tubes

The front face of the fabric is coated to enable to have vivid colors and good printing quality with SOLVENT, LATEX & UV inks.

(Test printing is suggested before the printing job.)



Ink  
Type



Solvent  
Printable



UV  
Printable



Latex  
Printable

\*Optional



Fire  
Retardant



Fire  
Retardant



Fire  
Retardant



Fire  
Retardant



Fire  
Retardant



Cutting



Cold Cut

All above released specifications and informations are for guidance purposes only. Our policy of continuous improvement may result in changes , we therefore reserve the right to alter the specifications and the informations at anytime without notice.